


CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts

## US1A THRU US1M

### DO-214AC (SMA)

#### FEATURES

- Plastic package has underwrites laboratory flammability Classification 94V-0
- Built-in strain relief, ideal for automated placement
- Glass passivated chip junction
- Fast switching for high efficiency
- High temperature soldering  
260 /10 second



Dimensions in inches and (millimeters)

#### MECHANICAL DATA

- Case: JEDED DO-214AC molded plastic over glass passivated chip
- Terminals: Solder plated, solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Weight: 0.002ounce, 0.064 gram

#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25 °C ambient temperature unless otherwise specified.
- Single phase, half wave, 60Hz, resistive or inductive load.
- For capacitive load derate current by 20%.

	SYMBOLS	US1A	US1B	US1D	US1G	US1J	US1K	US1M	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current At $T_A=55$	$I_{(AV)}$	1.0							Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC Method)	$I_{FSM}$	30							Amps
Maximum Instantaneous Forward Voltage per at 1.0A	$V_F$	1.0		1.30		1.70			Volts
Maximum DC Reverse Current at rated DC Blocking Voltage	$T_A = 25$	5.0							A
	$T_A = 125$	100							
Typical Reverse Recovery Time Test conditions $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$	$t_{rr}$	50				100			nS
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	$C_J$	20				15			pF
Typical Thermal Resistance (Note 1)	$R_{\theta JA}$	88							/W
	$R_{\theta JL}$	28							
Operating Junction Temperature	$T_J$	(-55 to +150)							
Storage Temperature Range	$T_{STG}$	(-55 to +150)							

#### Notes:

1. Thermal resistance from Junction to ambient and from junction to lead mounted on P.C.B. with 0.2×0.2" (5.0 × 5.0mm) copper pad areas.

CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 Volts

**US1A THRU US1M**

RATING AND CHARACTERISTIC CURVES US1A Thru US1M

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES : 1.Rise Time=7ns max. Input Impedance= 1 magohm. 22pF  
 2.Rise time=10ns max. Source Impedance= 50 ohms

SET TIME BASE FOR 50/100ns/cm