

CURRENT 10 Ampere  
VOLTAGE RANG 40 to 200 Volts


## MBR1040FAC THRU MBR10200FAC

### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O. Flame Retardant Epoxy Molding Compound.
- Metal silicon junction, majority carrier conduction
- Low power loss, high efficiency.
- High current capability
- Guardring for overvoltage protection
- For use in low voltage, high frequency inverters free wheeling, and polarity protection applications.
- In compliance with EU RoHS 2002/95/EC directives

### MECHANICAL DATA

- Case: ITO-220AB molded plastic
- Terminals: solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: As marked.
- Mounting Position: Any
- Weight: 0.055 ounces, 1.56 grams.



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

PARAMETER	SYMBOL	MBR 1040FAC	MBR 1045FAC	MBR 1050FAC	MBR 1060FAC	MBR 1080FAC	MBR 1090FAC	MBR 10100FAC	MBR 10150FAC	MBR 10200FAC	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	40	45	50	60	80	90	100	150	200	V
Maximum RMS Voltage	$V_{RMS}$	28	31.5	35	42	56	63	70	105	140	V
Maximum DC Blocking Voltage	$V_{DC}$	40	45	50	60	80	90	100	150	200	V
Maximum Average Forward Current (See fig.1)	$I_{F(AV)}$	10									A
Peak Forward Surge Current :8.3ms single half sine-wave superimposed on rated load(JEDEC method)	$I_{FSM}$	150									A
Maximum Forward Voltage at 10A, per leg	$V_F$	0.7		0.75		0.8		0.9			V
Maximum DC Reverse Current $T_j=25^\circ\text{C}$ at Rated DC Blocking Voltage $T_j=125^\circ\text{C}$	$I_R$	0.05 20									mA
Typical Thermal Resistance	$R_{\theta JC}$	2									$^\circ\text{C} / \text{W}$
Operating and Storage Junction Temperature Range	$T_j, T_{STG}$	-55 to + 150				-65 to + 175					$^\circ\text{C}$

Notes :


Both Bonding and Chip structure are available.

CURRENT 10 Ampere


VOLTAGE RANG 40 to 200 Volts

**MBR1040FAC THRU MBR10200FAC**


**RATING AND CHARACTERISTIC CURVES**




**Fig.1- FORWARD CURRENT DERATING CURVE**



**Fig.2- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTIC**



**Fig.3- TYPICAL REVERSE CHARACTERISTICS**



**Fig.4- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**